



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Filler.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park
Dodworth, Barnsley
Souty Yorkshire S75 3SP
Tel: 01226 771600 Fax: 01226 771601
www.siroflex.co.uk

E-mail address technical.siroflex@bostik.com

United Kingdom +44 (1226) 771600 (Office Hours Only)

Ireland

NPIC - National Poison Information Centre
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)
112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word

None

Hazard statements

Not classified

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction
EUH210 - Safety data sheet available on request

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	40 - <80	^		[4]
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	Carc. 2 (H351i)		01-2119489379-17-XXXX
Ethylene glycol	203-473-3	107-21-1	0.1 - <1	STOT RE 2 (H373) Acute Tox. 4 (H302)		01-2119456816-28-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.0015 - <0.01	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1)	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of toxic and corrosive gases/vapours.
Hazardous combustion products	Carbon dioxide (CO ₂). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.
Other information	Ventilate the area. Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

7.3. Specific end use(s)

Specific Use(s)
Filler.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Ashes (residues), cenospheres 93924-19-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³

Derived No Effect Level (DNEL) No information available

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

Derived No Effect Level (DNEL)			
Quartz (14808-60-7)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m ³	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m ³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	7 mg/m ³	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

Predicted No Effect Concentration No information available.

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

(PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l
Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	37 mg/kg dry weight
Marine sediment	3.7 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour See section 1 for more information
Odour Characteristic
Odour threshold No information available

Property	Values	Remarks • Method
pH	7 - 9	
Melting point / freezing point	= 0 °C	
Boiling point / boiling range	= 100 °C	
Flash point	No data available	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

Vapour pressure	No data available
Relative vapour density	No data available
Relative density	No data available
Water solubility	Miscible in water
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	> 21 mm ² /s
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	0.38% 8.4g/l
Density	1.66

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

Inhalation Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Ethylene glycol 107-21-1	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	
reaction mass of 5-chloro-2-methyl-2H-isothiazol 1-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Component Information					
Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion					Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
---------------	----------------

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY

Date: 06.10.2023

Replaces: 22.06.2022

Ref: 0317.5.BB/DL

Titanium dioxide 13463-67-7	Carc. 2
--------------------------------	---------

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic
Inhalation Xu et al (2010), carcinogenic activity of nanoscale TiO ₂ administered by an intrapulmonary spraying (IPS) - initiation-promotion protocol in rat lung	Rat	Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneri ella subcapitata)	LC50 96 h = 16000 mg/L (Poecilia reticulata static)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchner iella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz 14808-60-7	-	0
Ethylene glycol 107-21-1	-1.36	-
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.7	6.95
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
Ethylene glycol 107-21-1	The substance is not PBT / vPvB PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY
Date: 06.10.2023

Replaces: 22.06.2022
Ref: 0317.5.BB/DL

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed
H302 - Harmful if swallowed
H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Nov-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

SX CONTRACTORS MORTAR REPAIR CEMENT - CEMENT GREY

Date: 06.10.2023

Replaces: 22.06.2022

Ref: 0317.5.BB/DL

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet