



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC**  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** Not to be used in production of toys or childcare articles

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Siroflex Limited  
Dodworth Business Park, Dodworth Barnsley,  
South Yorkshire, S75 3SP  
Tel: +44 (1226) 771600 Fax: +44 (1226) 771601  
www.siroflex.co.uk

**E-mail address** info.siroflex@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1226) 771600 (Office Hours Only)  
**Ireland** **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
**Europe** 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

**Signal word**  
None

**Hazard statements**  
This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

[C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

## 2.3. Other hazards

No information available.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	[C]	-	01-2119489379-17-XXXX
Ethylene glycol	203-473-3	107-21-1	0.1 - <1	STOT RE 2 (H373) Acute Tox. 4 (H302)	-	01-2119456816-28-XXXX
Diethylene glycol monobutyl ether	203-961-6	112-34-5	0.1 - <1	Eye Irrit. 2 (H319)	-	01-2119475104-44-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.01 - <0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411)	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

				Aquatic Chronic 1 (H410)		
--	--	--	--	-----------------------------	--	--

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	IF exposed or concerned: Get medical advice/attention. Remove to fresh air.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and water.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	No information available.
-----------------	---------------------------

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Treat symptomatically.
------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	No information available.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	No information available.
<b>Hazardous combustion products</b>	Carbon oxides. Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ).

### 5.3. Advice for firefighters

<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

## SECTION 6: Accidental release measures

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation.  
**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.  
**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.  
**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.  
**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep from freezing.  
**Recommended storage temperature** Do not freeze. Keep at temperatures between 5 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

**Exposure Limits** This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup>

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

Ethylene glycol 107-21-1	TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> *	STEL: 12 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> Sk*
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm TWA: 67.5 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 67.5 mg/m <sup>3</sup> STEL: 15 ppm STEL: 101.2 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m <sup>3</sup>	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term	Inhalation	7 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

Local health effects			
----------------------	--	--	--

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.  
(PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>Ethylene glycol (107-21-1)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	37 mg/kg dry weight
Marine sediment	3.7 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Suitable protective clothing.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Solid  
**Appearance** Paste  
**Colour** See section 1 for more information

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

**Odour** Characteristic.  
**Odour threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	= 0 °C	
<b>Initial boiling point and boiling range</b>	= 100 °C	
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	7 - 9	
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	> 21 mm <sup>2</sup> /s	
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	No data available	Miscible in water
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Liquid Density</b>	1.57	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

## 9.2. Other information

**VOC Content (%)** 1.18% 19.0 g/l

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.  
    **Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## 10.4. Conditions to avoid

Conditions to avoid Do not freeze.

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.  
**Eye contact** Based on available data, the classification criteria are not met.  
**Skin contact** Based on available data, the classification criteria are not met.  
**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	> 2.5 mg/L ( Rat ) 6 h
Diethylene glycol monobutyl ether	=5660 mg/kg (Rattus)	= 2700 mg/kg (Oryctolagus cuniculus)	-
1,2-benzisothiazol-3(2H)-one [BIT]	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	ATE = 0.25 mg/L
reaction mass of 5-chloro-2-methyl-2H-isothiazol 1-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	-	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneri ella subcapitata)	LC50 96 h = 16000 mg/L (Poecilia reticulata static)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
Diethylene glycol monobutyl ether 112-34-5	EC50: >100mg/L (96h, Desmodesmus subspicatus)	LC50: =1300mg/L (96h, Lepomis macrochirus)	-	EC50: =2850mg/L (24h, Daphnia magna) EC50: >100mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchner iella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation**

### Component Information

Chemical name	Partition coefficient
Ethylene glycol	-1.36
Diethylene glycol monobutyl ether	1
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Ethylene glycol	The substance is not PBT / vPvB PBT assessment does not apply
Diethylene glycol monobutyl ether	The substance is not PBT / vPvB PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.
<b>Contaminated packaging</b>	Do not reuse empty containers.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### **Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diethylene glycol monobutyl ether	112-34-5	55. 75.

CAS 112-34-5 restricted for use in aerosol products sold to general public. Products for general public with level above 3% should be labeled "Do not use in paint spraying equipment".

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

#### National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

## Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H310 - Fatal in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H373 - May cause damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects

### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 28-Jun-2022

### Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

SX DECORATORS RAINPROOF EXTERIOR CAULK ACRYLIC  
Date: 06.06.2023

Replaces: 24.01.2022  
Ref: 0185.11.BB/DL

---

End of Safety Data Sheet